



MANNOL Automatic ATF Dexron II 8205

A universal all-season mineral-based transmission fluid (ATF) for automatic gearboxes, hydraulic power steering systems, cab tilt mechanisms, car hydraulic clutches and other hydraulic devices, including the ones operating under heavy-duty conditions in trucks and off-road vehicles. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy. It was developed on the basis of the requirements set by the GM group.

Product properties:

- The high-quality low-viscosity base in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45 °C) temperatures in winter and ensures a stable oil film under extreme loads and at high temperatures in summer;
- The high-technology combination of additives ensures good antifriction properties for gear couplings and required friction properties for friction elements thus ensuring a significant fuel economy, a continuous and smooth transmission shift and an extended service life of all transmission elements. It prevents scuffing;
- It has an increased thermal-oxidative stability and resistance to the high-temperature thermal degradation allowing decreasing the sludge formation, increasing the time between oil changes and reducing equipment maintenance costs;
- It protects metal parts from ferrous and non-ferrous alloys from corrosion when both in and not in operation;
- It effectively resists aeration and foam formation;
- It provides a compatibility with sealing materials, prevents them from swelling, hardening and shrinking that allows reducing the costs for spare parts and prevents leakages;
- It reduces noise.

It is recommended for automatic gearboxes of passenger cars and commercial vehicles requiring the oil of ATF Type Dexron-IID quality, it is mixed with brands of similar quality.

Colour: red.

Comply with the manufacturer's instructions provided in the user's manual!

Specifications

Approval

Recommendation

ALLISON C4
CATERPILLAR TO-2
GM Dexron II D
MAN 339 V1
MAN 339 Z1
MB 236.5
MB 236.7
RENK
VOITH H 55.6335.xx (G607)
ZF TE-ML 03D
ZF TE-ML 04D
ZF TE-ML 11A
ZF TE-ML 14A
ZF TE-ML 17C

PACKAGING

1L	MN8205-1	Plastic	20 pcs/box
1000L	MN8205-IBC	Pallet tank	
208L	MN8205-DR	Drum	
60L	MN8205-60	Drum	
20L	MN8205-20	Plastic	
10L	MN8205-10	Plastic	
4L	MN8205-4	Plastic	4 pcs/box