



## MANNOL ATF AG52 8211

A special all-season synthetic transmission fluid (ATF) for modern 4-5-speed automatic transmission gearboxes of the ZF Group. It is not suitable for 6-speed automatic transmissions. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of transmissions and fuel economy even under maximum loads. It was developed taking into account special requirements of the group VW G 052 162.

## Product properties:

- The high-quality low-viscosity synthetic base with a high viscosity index in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45 °C) temperatures in winter and ensures a stable oil film under maximum loads and at high temperatures in summer;

The high-technology combination of additives ensures good antifriction properties for gear couplings and excellent friction properties for friction elements thus ensuring a significant fuel economy, a continuous and smooth transmission shift and the extended service life of all transmission elements. It ensures a coordinated and smooth operation of clutches. It prevents scuffing;
It has a high thermal-oxidative and chemical stability and resistance to the high-temperature thermal degradation throughout the entire service life. It allows reducing lacquering, formation of sludge, soot and other carbon deposits, increasing the time between oil changes and ensuring the durability of transmission components thus reducing the equipment maintenance costs;
Due to the addition of special inhibitors, it protects metal parts from ferrous and non-ferrous alloys from corrosion when both in and not in operation;
It resists aeration and foam formation, as well as cavitation, has excellent cooling properties;

- It ensures a compatibility with all sealing materials, prevents them from swelling, hardening and shrinking that allows reducing the costs for spare parts and prevents leakages;

- It reduces noise.

It is recommended for use in any modern automatic transmissions (in manual operation, serial mode, electronic control – including with a hydraulic converter lock-up) of Volkswagen, Audi, Seat, Skoda vehicles in which the compliance with VW TL 521 62 requirements is required.

Colour: yellow

Comply with the manufacturer's instructions provided in the user's manual!

## **Specifications**

JASO M315 Type 1A Approval Recommendation MB 236.1 MB 236.2 MB 236.5 MB 236.6 MB 236.7 MB 236.8 MB 236.9 MB 236.91 MB 236.10 MB 236.11 MB ATF 3403-M115 MB A 0019892203 VOLKSWAGEN LT 71141 VOLKSWAGEN G 052 162 [AG4] VOLKSWAGEN G 052 990-A2 VOLKSWAGEN G 055 025-A2 VOLKSWAGEN G US 000 162 BMW ATF4 BMW ETL-7045 BMW ETL-7045 E BMW ETL-8072B **BMW LA 2634** BMW LT 71141 BMW 81 22 9 400 275 BMW 81 22 9 400 272 BMW 81 22 9 407 859 BMW 81 22 9 407 858 BMW 83 22 0 024 249 BMW 83 22 0 024 359 BMW 83 22 0 026 922 BMW 83 22 0 402 413 BMW 83 22 0 403 249 BMW 83 22 0 403 248 BMW 83 22 2 220 442 BMW 83 22 2 220 440 BMW 83 22 2 220 438 BMW 83 22 7 542 290 BMW 83 22 9 407 765 BMW 83 22 9 407 807 MINI 83 22 0 402 413 MINI ATF JWS 3309 JAGUAR JLM 20238 JAGUAR JLM 20292 JAGUAR JLM 21044 JAGUAR Jatco 3100 PL085 JAGUAR K17 JAGUAR LT 71141 JAGUAR WSS-M2C922-A1 LAND ROVER ATF N402 LAND ROVER JWS 3309US PEUGEOT Z 000169756 **RENAULT DP-0 RENAULT Matic D2 RENAULT SATF-D** ZF LifeguardFluid 5 (ZF No. S671 090 170) ZF TE-ML 05L ZF TE-ML 11A ZF TE-ML 11B

ZF TE-ML 21L AUDI LT 71141 AUDI G 052 162 [AG4] AUDI G 052 990-A2 AUDI G 055 025-A2 AUDI G US 000 162

## PACKAGING

	MN8211-1		
208L	MN8211-DR	Drum	
60L	MN8211-60	Drum	
20L	MN8211-20	Plastic	
10L	MN8211-10	Plastic	
4L	MN8211-4ME	Plastic	4 pcs/box
	MN8211-4		
1L	MN8211-1ME	Plastic	20 pcs/box