



MANNOL ATF CVT 8216

A special synthetic gear oil for CVT (Continuously Variable Transmission) – variable-speed gears. It was specially developed for use in continuously variable transmissions with a rigid articulated chain or a steel pull chain. It ensures a flawless operation of an automatic gearbox, guarantees minimal wear, a lasting service life of a transmission and fuel economy.

Product properties:

- The highest-quality unique high-viscosity synthetic base with a high viscosity index in combination with a multifunctional additive package preserves all its properties in a wide range of temperatures: it ensures good lubricating properties at low (-45 °C and lower) temperatures in winter and ensures a stable oil film under extreme loads and at high temperatures in summer;
- The high-technology combination of additives ensures superior friction properties for the chain thus ensuring a significant fuel economy, a continuous and smooth transmission shift and an extended service life of all transmission elements;
- It provides an excellent compatibility with sealing materials, prevents them from swelling, hardening and shrinking thus reducing the costs for spare parts and preventing leakages;
- It has an increased thermal-oxidative and chemical stability and resistance to the high-temperature thermal degradation throughout the entire service life. It allows reducing lacquering, formation of sludge, soot and other carbon deposits, increasing the time between oil changes and ensuring the durability of transmission components thus reducing the equipment maintenance costs;
- Due to the addition of special inhibitors, it effectively protects metal parts from ferrous and non-ferrous alloys from corrosion when both in and not in operation;
- It effectively resists aeration, the foam formation and cavitation, has excellent cooling properties; It has low loss by evaporation;
- It reduces noise.

The oil is a service product that requires a professional approach to selection. Its selection depends on the type of a variable-speed gear instead of the make of a vehicle. The oil has been tried and proved to be effective especially in Autotronic Mercedes-Benz Class A and B gearboxes, and in continuously variable automatic transmissions (Multitronic) in Audi vehicles. Colour: yellow-brown.

Specifications

Approval

Recommendation

VOLKSWAGEN G 052 180

VOLKSWAGEN G 052 180

BMW 83 22 0 429 154
BMW 83 22 0 429 154
BMW CVT EZL 799A
BMW CVT EZL 799A
CHRYSLER CVT FLUID NS-2
CHRYSLER CVT FLUID NS-2
DAIHATSU AMIX CVT FLUID DC
DAIHATSU AMIX CVT FLUID DC
FORD WSS M2C928-A
FORD WSS M2C928-A
FORD WSS M2C933-A
FORD WSS M2C933-A
FORD CVT FLUID 23
FORD CVT FLUID 23
FORD CVT FLUID 30
FORD CVT FLUID 30
FORD Mercon C
FORD Mercon C
GM DEX-CVT
GM DEX-CVT
HONDA HMMF (08260-99904)
HONDA HMMF (08260-99904)
HONDA HCF-2
HONDA HCF-2
HYUNDAI ATF SP-III
HYUNDAI ATF SP-III
INFINITI
INFINITI
JEEP CVT FLUID NS-2
JEEP CVT FLUID NS-2
KIA ATF-SP-III
KIA ATF-SP-III
LEXUS
LEXUS
MAZDA CVT FLUID JWS 3320
MAZDA CVT FLUID JWS 3320
MB 236.20
MB 236.20
MINI CVT EZL 799A
MINI 83 22 0 429 154
MINI CVT EZL 799A
MINI 83 22 0 429 154
MITSUBISHI DIAQUEEN CVT FLUID J1
MITSUBISHI DIAQUEEN CVT FLUID J1
MITSUBISHI DIAQUEEN CVT FLUID J4
MITSUBISHI DIAQUEEN CVT FLUID J4
MITSUBISHI CVT ATF SP-III
MITSUBISHI CVT ATF SP-III
MOPAR CVTF +4
MOPAR CVTF +4
NISSAN CVT FLUID NS-1
NISSAN CVT FLUID NS-1
NISSAN NS-2 (KLE52-00004)
NISSAN NS-2 (KLE52-00004)
SUBARU CVT OIL FOR LINEARTRONIC (K0425Y0710)
SUBARU CVT OIL FOR LINEARTRONIC (K0425Y0710)
SUBARU i-CVT FLUID
SUBARU i-CVT FLUID

SUBARU i-CVT FLUID FG
 SUBARU i-CVT FLUID FG
 SUZUKI SCVT FLUID
 SUZUKI SCVT FLUID
 SUZUKI CVT OIL
 SUZUKI CVT OIL
 SUZUKI CVT FLUID GREEN 1
 SUZUKI CVT FLUID GREEN 1
 SUZUKI CVT FLUID GREEN 2
 SUZUKI CVT FLUID GREEN 2
 SUZUKI NS-2
 SUZUKI NS-2
 TOYOTA CVT FLUID TC
 TOYOTA CVT FLUID TC
 TOYOTA CVT FLUID FE
 TOYOTA CVT FLUID FE

PACKAGING

4L	MN8216-4	Plastic	4 pcs/box
	MN8216-IBC		
208L	MN8216-DR	Drum	
60L	MN8216-60	Drum	
20L	MN8216-20	Plastic	
10L	MN8216-10	Plastic	
	MN8216-1		